



Standard Features

- Galvanised Steel Acoustic Canopy
- Rental Skid Base
- Integrated Fork Pockets
- High Quality Powder Coat Finish
- Manual Sump Oil Drain Pump
- Door Open Stays
- Lockable Maintenance Access Doors
- Mechanical & Hot Component Guards
- Fully Bunded Base Frame
- Control Panel Viewing Window
- Sound Proofing - Rockwool
- Long Run Integrated Diesel Tank
- 50 Degree Cooling Package
- Anti Vibration Mounts
- Stainless Steel Locks & Hinges

Engine Specifications

Manufacturer	CUMMINS	Fuel Consumption 100% PRP	13.1 l/ph
Model	4BTA3.9-G2	Fuel Consumption 80 % PRP	9.8 l/ph
Engine Type	45 Cylinder Diesel	Fuel Consumption 50 % PRP	6.7 l/ph
Injection Type	direct injection	Displacement	8.3 Lt
Aspiration Type	Turbocharged	Compression Ratio	17.3:1
Bore and Stroke	102 mm x 120 mm		

Alternator Specifications

Manufacturer	Mecce Alte	Poles	4
Model	ECP32 2M4C	Insulation	H Class
Prime Amps perϕ	Amps	Voltage Regulator	DSR

Dimensions

Length	2400 mm	Width	1006 mm
Height	1650 mm	Weight (Excl Fuel)	1425 kg Excl Fuel

Controller

DSE 7320 MKII Controller (Standard)

Outlets

2 x 15A Single Phase, 1 x 32A 3Phase, 1 x 50A 3Phase